

152.0000 – SantoFlex

Absaug- & Gebläseschlauch bis + 150 °C
suction & blower hose up to + 150 °C



Material:

TPE-beschichtetes Polyestergewebe
Federstahlspirale

Temperaturbereich:

-40 °C bis + 150°C

Eigenschaften:

sehr gute Chemikalienbeständigkeit
wie Säure-, Laugen- oder Lösemitteldämpfe
dauerflexibel
UV- & ozonfest
verrottungsfest
leicht und hochflexibel

Einsatzmöglichkeiten:

Trocknungs- & Verbrennungsanlagen
für chemische Dämpfe

Lieferformen:

Ø 20 bis 500 mm
Farbe: schwarz
Aufmachung: 6 / 10 / 15 m

Andere Ausführungen:

SantoFlex se – schwer entflammbar gem. DIN 410
SantoFlex crash – überfahrbar

Preise finden Sie unter:

SantoFlex – 152.0000



Material:

TPE coated polyester fabric
spring steel wire

Temperature range:

-40 °C up to +150 °C

Properties:

very good chemical resistance
as fumes of acid, alkalis of solvents
long term flexible
uv & ozon resistant
rot resistant
lightweight and very flexible

Applications:

hot air hose for drying and combustion plants
for chemical fumes

Delivery forms:

Ø 20 up to 500 mm
colour: black
Length: 6 / 10 / 15 m

Other versions:

SantoFlex se – hard. inflam. in acc. to DIN 4102 B1
SantoFlex crash – crash proof

Prices you will find:

SantoFlex – 152.0000



Brückenschelle 801
Bridge clamp 801



Schnellverschluss 806
Quick release 806.



Verbinder 822.0
Joiner 822.0



Reduzierung 829.0
Reducer 829.0



152.0000 – SantoFlex

Absaug-& Gebläseschlauch bis + 150 °C
suction & blower hose up to + 150 °C

\emptyset in mm	Gewicht / weight in g/m	Biegeradius / bending radius in mm	Betriebsdruck / working pressure in bar	Unterdruck / vacuum in bar	Artikel-Nr. / article no.
20	80	20	0,450	0,250	152-020-0000
25	90	25	0,450	0,200	152-025-0000
30	140	30	0,400	0,200	152-030-0000
40	160	40	0,350	0,150	152-040-0000
50	210	50	0,350	0,100	152-050-0000
60	250	60	0,350	0,080	152-060-0000
70	290	70	0,300	0,080	152-070-0000
75	310	75	0,200	0,070	152-075-0000
80	330	80	0,200	0,060	152-080-0000
100	560	100	0,150	0,050	152-100-0000
120	670	120	0,150	0,040	152-120-0000
125	700	125	0,130	0,040	152-125-0000
140	730	140	0,120	0,040	152-140-0000
150	780	150	0,110	0,040	152-150-0000
175	820	175	0,090	0,030	152-175-0000
200	1270	200	0,080	0,020	152-200-0000
250	1600	250	0,070	0,020	152-250-0000
300	1450	300	0,050	0,010	152-300-0000
350	1550	350	0,040	0,010	152-350-0000
400	1780	400	0,040	0,010	152-400-0000
450	2000	450	0,030	0,010	152-450-0000
500	2250	500	0,030	0,010	152-500-0000

Alle Daten bei ca. +23 °C

All datas at ca. +23 °C

Zwischenabmessungen auf Anfrage möglich.

Dimensions between listed are possible on request.

