

# 152.4000 – ViperFlex

Absaug- & Gebläseschlauch bis + 130 °C  
suction & blower hose up to + 130 °C



**Material:**

TPE(EPDM)-beschichtetes Polyestergewebe  
Wandstärke ca. 0,4 mm, Federstahlspirale

**Temperaturbereich:**

-40 °C bis + 130°C

**Eigenschaften:**

sehr gute Chemikalienbeständigkeit  
wie Säure-, Laugen- oder Lösemitteldämpfe  
dauerflexibel  
UV- & ozonfest  
verrottungsfest  
leicht und hochflexibel

**Einsatzmöglichkeiten:**

Trocknungs- & Verbrennungsanlagen  
für chemische Dämpfe

**Lieferformen:**

Ø 22 bis 500 mm  
Farbe: schwarz  
Aufmachung: 10 / 15 m

**Preise finden Sie unter:**

ViperFlex – 152.4000



**Material:**

TPE (EPDM) coated polyester fabric  
wall thickness ca. 0,4 mm, spring steel wire

**Temperature range:**

-40 °C up to +130 °C

**Properties:**

very good chemical resistance  
as fumes of acid, alkalis of solvents  
long tem flexible  
uv & ozon resistant  
rot resistant  
lightweight and very flexible

**Applications:**

hot air hose for drying and combustion plants  
for chemical fumes

**Delivery forms:**

Ø 22 up to 500 mm  
colour: black  
Length: 10 / 15 m

**Prices you will find:**

ViperFlex – 152.4000



draht-klemme 805  
Wire clamp 805



Brückenschelle 801  
Bridge clamp 801



Schnellverschluss 806  
Quick release 806



Verbinder 822.0  
Joiner 822.0



Reduzierung 829.0  
Reducer 829.0



## 152.4000 – ViperFlex

Absaug- & Gebläseschlauch bis + 130 °C  
suction & blower hose up to + 130 °C

<b>Ø</b>	<b>Gewicht / weight</b>	<b>Biegeradius / bending radius</b>	<b>Betriebsdruck / working pressure</b>	<b>Unterdruck / vacuum</b>	<b>Artikel-Nr. / article no.</b>
<b>in mm</b>	<b>in g/m</b>	<b>in mm</b>	<b>in bar</b>	<b>in bar</b>	
22	80	22	0,450	0,250	152-022-4000
25	90	25	0,450	0,200	152-025-4000
32	140	32	0,400	0,200	152-032-4000
40	160	40	0,350	0,150	152-040-4000
50	210	50	0,350	0,100	152-050-4000
60	250	60	0,350	0,080	152-060-4000
70	290	70	0,300	0,080	152-070-4000
75	310	75	0,200	0,070	152-075-4000
80	330	80	0,200	0,060	152-080-4000
100	560	100	0,150	0,050	152-100-4000
120	670	120	0,150	0,040	152-120-4000
125	700	125	0,130	0,040	152-125-4000
140	730	140	0,120	0,040	152-140-4000
150	780	150	0,110	0,040	152-150-4000
175	820	175	0,090	0,030	152-175-4000
200	1270	200	0,080	0,020	152-200-4000
250	1600	250	0,070	0,020	152-250-4000
300	1450	300	0,050	0,010	152-300-4000
350	1550	350	0,040	0,010	152-350-4000
400	1780	400	0,040	0,010	152-400-4000
450	2000	450	0,030	0,010	152-450-4000
500	2250	500	0,030	0,010	152-500-4000

Alle Daten bei ca. +23 °C

All datas at ca. +23 °C

Zwischenabmessungen auf Anfrage möglich.

Dimensions between listed are possible on request.