

271.0400 SilPress / SilPress tt

Silikon-Druckschlauch bis +200 °C
silicone pressure hose up to +200 °C



Material:

Silikon-Wand, fadenverstärkt

Temperaturbereich:

-50 °C bis +200 °C

Eigenschaften:

lebensmittelecht gem. FDA und EU-Richtlinien
schwer entflammbar, konform zu UL 94 HB
innen und außen glatt
sehr gute mechan. Eigenschaften wie
Reißfestigkeit, Reißfestigkeit ...
biokompatibel
frei von Halogenen
sehr gute Gasdichtheit

Einsatzmöglichkeiten:

für Gase und Flüssigkeiten
chem. Industrie, Lebensmitteltechnik, Pharmazie

Lieferformen:

Ø 3 bis 20 mm, bis 25 m/Rolle
innen opak, außen rot

Auf Anfrage

Kurzlängen,
konfektion. auf Kundenwunsch mit Muffen ...
SilPress tt – innen und außen transparent

Preise finden Sie unter:

SilPress – 271.0400



Material:

silicone wall, reinforced by yarn

Temperature range:

-50 °C up to +200 °C

Properties:

food conform in acc. to rules of FDA and EU
hardly inflammable in acc. to UL 49 HB
smooth inside and outside
very good mechanical properties as
tensile strength, compression resistance ...
biocompatible
free of halogen
very good gas tight

Applications:

for vapours, liquids
chemical, foodstuff and pharmac. industry

Delivery forms:

Ø 3 up to 20 mm, up to 25 m/roll
inside opaque, outside red

On request:

short length
custom made solutions with cuffs, couplings ...
SilPress tt – in- and outside transparent

Prices you will find:

SilPress – 271.0400





271.0400
SilPress / SilPress tt

PU-Saug- & Gebläseschlauch bis +90 °C
PU suction & blower hose up to +90 °C

Innen-Ø inner Ø <i>in mm</i>	Wandstärke wall thickness <i>in mm</i>	Platzdruck / bursting pressure			Art.- Nr.: art.- no.:
		20 °C <i>in bar</i>	95 °C <i>in bar</i>	130 °C <i>in bar</i>	
3	2,5	82	76	40	271-003-0400
4	2,5	69	59	35	271-004-0400
5	3,0	55	41	30	271-005-0400
6	3,0-3,5	62	39	28	271-006-0400
7	3,2-3,5	56	37	27	271-007-0400
8	3,2-3,5	49	34	26	271-008-0400
9	3,5-3,8	47	33	25	271-009-0400
10	3,5-4,0	44	32	24	271-010-0400
11	3,5-4,0	42	31	23	271-011-0400
12	3,5-4,0	39	29	22	271-012-0400
13	4,0-4,5	38	28	22	271-013-0400
14	4,0-4,5	37	28	21	271-014-0400
15	4,0-4,5	36	27	21	271-015-0400
16	4,0-4,5	35	26	21	271-016-0400
17	4,0-4,5	34	25	20	271-017-0400
18	4,0-4,5	33	24	20	271-018-0400
19	4,0-4,5	32	24	20	271-019-0400
20	5,0-5,5	31	23	19	271-020-0400

Alle Daten bei ca. +23 °C
 All datas at ca. +23 °C

Zwischenabmessungen auf Anfrage möglich.
 Dimensions between listed are possible on request.